



TELESCOPING FLAGPOLES

For Technical Support visit us at www.sunsetter.com/ownerscorner
or Call Toll Free 800-670-7071 • Fax 877-224-4944

Tube #3 Assembly Replacement Instructions

Tools Needed: Phillips Screwdriver

Parts Supplied: Tube #3 Assembly

WARNING: FAILURE TO FOLLOW THESE INSTRUCTIONS CAN RESULT IN PERSONAL INJURY! PLEASE READ THESE INSTRUCTIONS COMPLETELY BEFORE PERFORMING THIS PROCEDURE.

1. Remove the top two sections of the pole by holding in the middle Spring Button while extending the two sections upwards and sliding them out of tube #3.
2. Remove tube #3 from tube #4 by first lifting tube #3 until the Spring Button locks. Next depress the Spring Button and remove tube #3 completely out of tube #4.
3. Place the new tube #3 back into tube #4. Lower it slowly until the Spring Button pops out of the hole in tube #4. Be sure to line up the slot in the Bottom Cap with the track on the inside of the tube.
4. Place the two top sections back into tube #3. Lower them slowly until the Spring Button pops out of the hole in tube #3. Be sure to line up the slot in the Bottom Cap with the track on the inside of the tube.
5. Test the Flagpole for proper operation.

