



RETRACTABLE AWNINGS

For Technical Support visit us at www.sunsetter.com/ownerscorner or Call Toll Free 800-670-7071 • Fax 877-224-4944

Lateral Awning Removal Procedure

Helper needed

Tools needed: 1/2" socket or wrench, 7/16" socket or wrench, ladders, (2) plastic safety sleeves (supplied)

WARNING: FAILURE TO FOLLOW THESE INSTRUCTIONS COULD RESULT IN PERSONAL INJURY!

- 1. Close the Awning completely.
2. Unplug the Awning motor cord, if equipped.
3. Install the Plastic Safety Sleeves on both Lateral Arms to prevent them from extending. See Figure 1.

WARNING: DO NOT ATTEMPT TO REMOVE THE AWNING WITHOUT INSTALLING THE PLASTIC SAFETY SLEEVES ON BOTH LATERAL ARMS.

- 4. Using a 1/2" socket or wrench, check that all 8 fasteners are tight, on the right and left side of the Awning (Arm Clamps - 2 each, Roller Brackets - 1 each, and Front Bar Connectors- 1 each). See Figure 2.
5. For Motorized Awnings- Using a 7/16" socket or wrench, check that the 2 bolts that secure the Motor to the Roller Bracket are tight. See Figure 2.
6. While your Helper keeps the Awning in the Mounting Brackets, carefully remove the Retaining Bolts, Nuts and Washers from each Mounting Bracket (Soffit or Wall). See Figure 2a.
7. Using the appropriate help, carefully remove the Awning from the Mounting Brackets and place on a stable surface.

CAUTION: Be careful not to drag the Awning on any surface as you can damage the Fabric or painted surfaces.

