



TELESCOPING FLAGPOLES

For Technical Support visit us at ownerscorner.sunsetter.com
or Call Toll Free 800-670-7071 • Fax 877-224-4944

Tube #1 Replacement Instructions

Tools Needed: Adjustable wrench

Parts Supplied: Tube #1 Assembly (FP006-1)

WARNING: THE METAL PARTS COULD HAVE SHARP EDGES. TO PREVENT THE RISK OF INJURY, USE SAFETY GLOVES WHEN REMOVING OR REPLACING PARTS. FAILURE TO DO SO COULD CAUSE PERSONAL INJURY.

WARNING: FAILURE TO FOLLOW THESE INSTRUCTIONS CAN RESULT IN PERSONAL INJURY! PLEASE READ THESE INSTRUCTIONS COMPLETELY BEFORE PERFORMING THIS PROCEDURE.

1. Remove the top section of the pole by holding in the Spring Button while extending the section upwards and sliding it out of pole #2
2. Remove the Gold Ball by loosening the gold nut and unscrewing the Gold Ball. Remove the flag(s) and flag clips from the swivels.
3. Install the Gold Ball onto the new pole section.
4. Align the slot in the Bottom Cap of tube #1 with the track inside of tube #2.
5. Lower the top section into tube #2 while holding in the Spring Button in tube #1.
6. Reinstall the flag(s) with the flag clips.
7. Test the Flagpole for proper operation.

